



CERTIFIED

Genset : GB/T2820-2009, ISO8528.
Engine : ISO 2046, DIN 6271.
Alternator : VDE 0530, NEMA MGI-32, IEC34, AS1359.

FEATURES

BAUDOUIN Heavy-Duty Engine
Rugged industrial diesel delivers reliable power, low emissions and fast response to load changes.

LEROY-SOMER Brushless Alternator
Low reactance 2/3 pitch windings; low waveform distortion with non-linear loads, fault clearing short-circuits capability, and class H insulation.

Control System
DeepSea electronic control is the industry leading standard equipment and provides total genset system integration, including automatic remote starting/stopping, precise voltage regulation, alarm and status message display.

Cooling System
Standard integral set-mounted radiator system, designed and tested for rated ambient temperatures, simplifies facility design requirements for rejected heat.

Enclosures
Optional weather-protective and soundattenuated enclosures are available.

Warranty
Backed by a comprehensive warranty and nation wide distributor network.

Emergency Standby Power (ESP)
Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. Emergency Standby Power (ESP) is in accordance with ISO 8528. Fuel Stop power in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.

Limited-Time Running Power (LTP)
Applicable for supplying power to a constant electrical load for limited hours. Limited Time Running Power (LTP) is in accordance with ISO 8528.

Prime Power (PRP)
Applicable for supplying power to varying electrical load for unlimited hours. Prime Power (PRP) is in accordance with ISO 8528. Ten percent overload capability is available in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.

Base Load (Continuous) Power (COP)
Applicable for supplying power continuously to a constant electrical load for unlimited hours. Continuous Power (COP) in accordance with ISO 8528, ISO 3046, AS 2789, DIN 6271 and BS 5514.

POWER RATING

SERVICE		PRP	ESP
POWER	kVA	1125	1250
POWER	kW	900	880
RATED SPEED	r.p.m	1500	
MAIN TENSION	V	400	
FREQUENCY	Hz	50	

STANDARD SOUNDPROOFING



HSD (High Speed Diesel)



Water Cooling



Three Phase



50 Hz



Diesel

TRUPOWER has the right to modify any features without prior notice.

Weight and dimensions based on standard products. Illustrations may include optional equipment.

Technical data described in this catalogue correspond to the available information at the moment of printing

The illustrations and image are indicative and may not coincide in their entirety with the product

ENGINE



Rated Engine Output (PRP)	kW	950
Rated Engine Output (ESP)	kW	1051
Manufacturer	BAUDOUIN	
Model	12M33G1250/5	
Engine Type	4-stroke diesel	
Injection Type	Direct	
Aspiration Type	kVA	Turbocharged and Aftercooled

ENGINE SPECIFICATIONS



Number of cylinders and arrangement	L	12-V
Bore and Stroke	mm	150 x 185
Displacement	L	39.2
Cooling System	Liquid (water + 50% antifreeze)	
Lube Oil Specifications	15W40 CF4	
Compression Ratio	15:01	
Air Filter Type	Dry	

- Diesel engine
- 4-stroke cycle
- Water-cooled
- 12V electrical system
- Water separator filter (visible level)
- Dry air filter
- Radiator with pusher fan
- Electronic governor



ALTERNATOR



Manufacturer	LEROY-SOMER
Model	LSA50.2M6
Poles	No. 4
Connection type	(Standard) Series Star
Insulation	Class H
Enclosure (According IEC-34-5)	IP23

ALTERNATOR SPECIFICATIONS



Exciter system	Self-excited, brushless
Voltage regulator A.V.R. (Electronic)	D350
Bracket type	Single bearing
Coupling system	Flexible disc
Coating type	Standard (Vacuum impregnation)


- Self-Excited / Aux winding
- IP23 protection
- H class insulation

WEIGHT AND DIMENSION



		OPEN	SILENT
*Max shipping volume	m3	25.60	31.61
*Length (L)	mm	4800	5900
*Width (W)	mm	2195	2340
*Height (H)	mm	2430	2290
*Weight	Kg	7840	11270
*Wet Weight	Kg	11382	14812
*Autonomy (100% PRP)	Hours	6	6

*Approx dimension, custom units may slightly vary



APPLICATION DATA

EXHAUST SYSTEM

Maximum exhaust temperature	°C	750
Exhaust Gas Flow	m³/min	225.1
Maximum allowed back pressure	mBar	75
Exhaust Flange Size (external diameter)	mm	200

FUEL CONSUMPTION

Fuel Consumption ESP	L/h	262.6
Fuel Consumption 100% PRP	L/h	236.2
Fuel Consumption 75% PRP	L/h	175
Fuel Consumption 50% PRP	L/h	119.5

STARTING TIME

Recommended battery	Ah	125
Auxiliary Voltage	Vdc	12

NECESSARY AMOUNT OF AIR

Intake air flow	litre/sec	74.1
Alternator cooling air flow	m³/s	1430

FUEL SYSTEM

Fuel Oil Specifications		Diesel
Fuel Tank Standard	L	1417

- Steel chassis
- Anti-vibration shock absorbers
- Chassis with integrated fuel tank
- Fuel level gauge
- External emergency stop switch
- Bodywork made from high quality steel plate
- High mechanical strength
- Low noise emissions level
- Soundproofing provided by high-density material
- Powder coating
- Full access for maintenance (water, oil and filters, no need to remove the canopy)
- Fuel tank drain plug
- Reinforced lifting hooks for crane hoisting
- Oil sump extraction kit
- IP Protection according to ISO 8528-13:2016